

MSC 1000 FCE

USO INTENSIVO

FULL
OIL

MADE IN ITALY CE



DATI TECNICI | DATA SHEETS | FICHE TECHNIQUE | DATOS TECNICOS

MSC 1000 FCE FULL OIL

Tensione alimentazione Power supply Tension alimentation Tensione de alimentaci3n*	230 Vac - 50/60 Hz
Motore elettrico Electric motor Moteur 6lectrique Motor electrico (rpm)	1400
Corrente Current Courant Corriente (A)	1,7 A
Potenza motore Motor power Puissance moteur Potencia motore (W)	550 W
Termoprotezione Thermal protection Protection thermique Protecci3n t6rmica	150°
Condensatore Capacitor Condensateur Condensador	18 µf
Forza di spinta Thrust force Force de pouss6e Fuerza de empuje	1000 N
Rapporto di riduzione Mechanical reduction Rapport de r6duction Reducci3n mec6nica	1:30
Pignone Pinion Pignon Pi3n3n	modulo 4 - Z16
Lubrificazione - FULL OIL Lubrication - FULL OIL Lubrification - PLEIN D'HUILE Lubrification - ba3o DE ACEITE	1,1 L
Temp. di funzionamento Operating temperature Temp. de fonctionnement Temp. ambiente	-20°C + 55°C
Grado di protezione Class protection Classe de protection Grado de protecci3n	IP 44
Frizione Clutch Embrayage Embrague	no
Finecorsa Limit switch Hauteur Final de carrera	magnetico
Velocità cancello Speed gate Vitesse portail Velocidad puerta corredera	9,6 m/min
Altezza pignone - pavimento - cremagliera Height pinion - floor - rack Hauteur pignon - plancher - cr6maill6re Altura pi3n3n - suelo - cremallera	98 mm
Peso cancello Weight gate Poid portail Peso puerta corredera	1000 Kg
Peso motoriduttore Weight gearmotor Poid motoreducteur Peso motor	17,5 Kg
Dimensioni Dimensions Dimensions moteur Medidas (L x P x H) mm	290 x 210 x 335

* Disponibile | Available | Disponible | Disponible: 110 Vac - 60 Hz | 115 Vac - 60 Hz | 127 Vac - 60 Hz

DOTAZIONI DI SERIE | STANDARD EQUIPMENT 6QUIPEMENT STANDARD | EQUIPAMIENTO ESTANDAR

PF

Piastra di fissaggio
Fixing plate
Plaque de fixation
Placa de fijaci3n



MSC 1000 FCE FULL OIL

Altre viste
Other views
Autres vues
Otras vistas



MSC 2000 FCM

USO INTENSIVO

automatismi per cancelli scorrevoli | automatism for sliding gates | automatisme pour portails coulissants | automatismos para puertas correderas

MADE IN ITALY



Anti-schiacciamento con frizione doppio disco a bagno olio
Anti - crushing with clutch double disk bath oil
Anti-écrasement avec embrayage double disque au bain huile
Anti-aplastamiento con embrague doble disco a baño en aceite



DATI TECNICI | DATA SHEETS | FICHE TECHNIQUE | DATOS TECNICOS

MSC 2000 FCM

Tensione alimentazione Power supply Tension alimentation Tensione de alimentación*	230 Vac - 50 60 Hz
Motore elettrico Electric motor Moteur électrique Motor eléctrico (rpm)	1400
Corrente Current Courant Corriente (A)	2,4 A
Potenza motore Motor power Puissance moteur Potencia motore (W)	650 W
Termoprotezione Thermal protection Protection thermique Protección térmica	150°
Condensatore Capacitor Condensateur Condensador	25 µf
Forza di spinta Thrust force Force de poussée Fuerza de empuje	2000 N
Rapporto di riduzione Mechanical reduction Rapport de réduction Reducción mecánica	1:30
Pignone Pinion Pignon Piñón	modulo 4 - Z16
Lubrificazione - FULL OIL Lubrication - FULL OIL Lubrification - PLEIN D'HUILE Lubrification - baño DE ACEITE	1,1 L
Temp. di funzionamento Operating temperature Temp. de fonctionnement Temp. ambiente	-20°C + 55°C
Grado di protezione Class protection Classe de protection Grado de protección	IP 44
Finecorsa Limit switch Hauteur Final de carrera	meccanico
Velocità cancello Speed gate Vitesse portail Velocidad puerta corredera	9,6 m/min
Altezza pignone - pavimento - cremagliera Height pinion - floor - rack Hauteur pignon - plancher - crémaillère Altura piñón - suelo - cremallera	98 mm
Peso cancello Weight gate Poids portail Peso puerta corredera	2000 Kg
Peso motoriduttore Weight gearmotor Poids motoreducteur Peso motor	17,8 Kg
Dimensioni Dimensions Dimensions moteur Medidas (L x P x H) mm	290 x 210 x 335

* Disponibile | Available | Disponible | Disponible: 110 Vac - 60 Hz | 115 Vac - 60 Hz | 127 Vac - 60 Hz

DOTAZIONI DI SERIE | STANDARD EQUIPMENT ÉQUIPEMENT STANDARD | EQUIPAMIENTO ESTANDAR

PF

Piastra di fissaggio
Fixing plate
Plaque de fixation
Placa de fijación



MSC 2000 FCM

Altre viste
Other views
Autres vues
Otras vistas



MSC 2500 FCM

USO INTENSIVO

automatismi per cancelli scorrevoli | automatismos for sliding gates | automatisme pour portails coulissants | automatismos para puertas correderas

MADE IN ITALY CE



Anti-schiacciamento con frizione doppio disco a bagno olio
Anti - crushing with clutch double disk bath oil
Anti-écrasement avec embrayage double disque au bain huile
Anti-aplastamiento con embrague doble disco a baño en aceite



DATI TECNICI | DATA SHEETS | FICHE TECHNIQUE | DATOS TECNICOS

MSC 2500 FCM

Tensione alimentazione Power supply Tension alimentation Tensione de alimentaciòn*	230 Vac - 50/60 Hz
Motore elettrico Electric motor Moteur électrique Motor electrico (rpm)	1400
Corrente Current Courant Corriente (A)	2,8 A
Potenza motore Motor power Puissance moteur Potencia motore (W)	700 W
Termoprotezione Thermal protection Protection thermique Protección térmica	150°
Condensatore Capacitor Condensateur Condensador	31,5 µf
Forza di spinta Thrust force Force de poussée Fuerza de empuje	2500 N
Rapporto di riduzione Mechanical reduction Rapport de réduction Reducción mecánic	1:30
Pignone Pinion Pignon Piñón	modulo 4 - Z16
Lubrificazione - FULL OIL Lubrication - FULL OIL Lubrification - PLEIN D'HUILE Lubrification - baño DE ACEITE	1,1 L
Temp. di funzionamento Operating temperature Temp. de fonctionnement Temp. ambiente	-20°C + 55°C
Grado di protezione Class protection Classe de protection Grado de protección	IP 44
Finccorsa Limit switch Hauteur Final de carrera	meccanico
Velocità cancello Speed gate Vitesse portail Velocidad puerta corredera	9,6 m/min
Altezza pignone - pavimento - cremagliera Height pinion - floor - rack Hauteur pignon - plancher - crémaillère Altura piñón - suelo - cremallera	98 mm
Peso cancello Weight gate Poids portail Peso puerta corredera	2500 Kg
Peso motoriduttore Weight gearmotor Poids motoreducteur Peso motor	17,8 Kg
Dimensioni Dimensions Dimensions moteur Medidas (L x P x H) mm	290 x 210 x 335

* Disponibile | Available | Disponible | Disponible: 110 Vac - 60 Hz | 115 Vac - 60 Hz | 127 Vac - 60 Hz

DOTAZIONI DI SERIE | STANDARD EQUIPMENT

ÉQUIPEMENT STANDARD | EQUIPAMIENTO ESTANDAR

PF

Piastra di fissaggio
Fixing plate
Plaque de fixation
Placa de fijación



MSC 2500 FCM

Altre viste
Other views
Autres vues
Otras vistas

