

MSC 800 FCM

USO RESIDENZIALE

MADE IN ITALY CE



DATI TECNICI | DATA SHEETS | FICHE TECHNIQUE | DATOS TECNICOS

MSC 800 FCM

Tensione alimentazione Power supply Tension alimentation Tensione de alimentaci3n*	230 Vac - 50 60 Hz
Motore elettrico Electric motor Moteur 6lectrique Motor electrico (rpm)	1400
Corrente Current Courant Corriente (A)	1,7 A
Potenza motore Motor power Puissance moteur Potencia motore (W)	450 W
Termoprotezione Thermal protection Protection thermique Protecci3n t6rmica	130°
Forza di spinta Thrust force Force de pouss6e Fuerza de empuje	800 N
Pignone Pinion Pignon Pi3n3n	modulo 4 - Z16
Lubrificazione Lubrication Lubrification Lubrification	grasso fat graisse grasa
Temp. di funzionamento Operating temperature Temp. de fonctionnement Temp. ambiente	-20°C + 55°C
Grado di protezione Class protection Classe de protection Grado de protecci3n	IP 44
Frizione Clutch Embrayage Embrague	no
Finecorsa Limit switch Hauteur Final de carrera	meccanico
Velocità cancello Speed gate Vitesse portail Velocidad puerta corredera	12 m min
Altezza pignone - pavimento - cremagliera Height pinion - floor - rack Hauteur pignon - plancher - cr6maill6re Altura pi3n3n - suelo - cremallera	80 mm
Peso cancello Weight gate Poid portail Peso puerta corredera	800 Kg
Peso motoriduttore Weight gearmotor Poid motoreducteur Peso motor	9 Kg
Dimensioni Dimensions Dimensions moteur Medidas (L x P x H) mm	285 x 175 x 320

* Disponibile | Available | Disponible | Disponible: 110 Vac - 60 Hz | 115 Vac - 60 Hz | 127 Vac - 60 Hz

DOTAZIONI DI SERIE | STANDARD EQUIPMENT

6QUIPEMENT STANDARD | EQUIPAMIENTO ESTANDAR

PF

Piastra di fissaggio
Fixing plate
Plaque de fixation
Placa de fijaci3n



MSC 800 FCM

Altre viste
Other views
Autres vues
Otras vistas



MSC 600 FCM

USO RESIDENZIALE

automatismi per cancelli scorrevoli | automatismos for sliding gates | automatisme pour portails coulissants | automatismos para puertas correderas

MADE IN ITALY CE



DATI TECNICI | DATA SHEETS | FICHE TECHNIQUE | DATOS TECNICOS

MSC 600 FCM

Tensione alimentazione Power supply Tension alimentation Tensione de alimentaciòn*	230 Vac - 50 60 Hz
Motore elettrico Electric motor Moteur électrique Motor electrico (rpm)	1400
Corrente Current Courant Corriente (A)	1,5 A
Potenza motore Motor power Puissance moteur Potencia motore (W)	350 W
Termoprotezione Thermal protection Protection thermique Protección térmica	130°
Forza di spinta Thrust force Force de poussée Fuerza de empuje	600 N
Pignone Pinion Pignon Piñón	modulo 4 - Z16
Lubrificazione Lubrication Lubrification Lubrification	grasso fat graisse grasa
Temp. di funzionamento Operating temperature Temp. de fonctionnement Temp. ambiente	-20°C + 55°C
Grado di protezione Class protection Classe de protection Grado de protección	IP 44
Frizione Clutch Embrayage Embrague	no
Finecorsa Limit switch Hauteur Final de carrera	meccanico
Velocità cancello Speed gate Vitesse portail Velocidad puerta corredera	12 m min
Altezza pignone - pavimento - cremagliera Height pinion - floor - rack Hauteur pignon - plancher - crémaillère Altura piñón - suelo - cremallera	80 mm
Peso cancello Weight gate Poids portail Peso puerta corredera	600 Kg
Peso motoriduttore Weight gearmotor Poids motoreducteur Peso motor	8 Kg
Dimensioni Dimensions Dimensions moteur Medidas (L x P x H) mm	285 x 175 x 320

* Disponibile | Available | Disponible | Disponible: 110 Vac - 60 Hz | 115 Vac - 60 Hz | 127 Vac - 60 Hz

DOTAZIONI DI SERIE | STANDARD EQUIPMENT

ÉQUIPEMENT STANDARD | EQUIPAMIENTO ESTANDAR

PF

Piastra di fissaggio
Fixing plate
Plaque de fixation
Placa de fijación



MSC 600 FCM

Altre viste
Other views
Autres vues
Otras vistas

